

Combining Tables

Cartesian Product

Multiple tables in the FROM clause

There may be instances when a query requires information from two or more tables to be collated in some way, for example, to find out in which locations the employees work. This would require the information in the EMP table to be combined with information from the DEPT table.

To two or more tables together, SQL implements the equivalent of the mathematical operation *Cartesian Product*. This is written in SQL by listing the tables to be connected in the *FROM* clause, separated by commas.

A multi-table FROM statement is of the form:

```
FROM tablename [,tablename [,tablename ...
```

A query to combine the EMP and DEPT tables would look like this:

```
select *  
from EMP, DEPT;
```

In Relational Algebra the Cartesian Product would be shown as

$$EMP \times DEPT$$

This would produce the following results

EMPNO	ENAME	JOB	MGR	HIREDATE	SAL	COMM	emp.DEPTNO	dept.DEPTNO	DNAME	LOC
405	MARCH	ADMIN	938	13/06/1997	18000		2	1	ACCOUNTIN	LONDON
405	MARCH	ADMIN	938	13/06/1997	18000		2	2	RESEARCH	YORK
405	MARCH	ADMIN	938	13/06/1997	18000		2	3	SALES	BIRMINGHAM
405	MARCH	ADMIN	938	13/06/1997	18000		2	4	OPERATIONS	LEEDS
936	CASSY	ADMIN	734	23/07/2002	19500		3	1	ACCOUNTIN	LONDON
936	CASSY	ADMIN	734	23/07/2002	19500		3	2	RESEARCH	YORK
936	CASSY	ADMIN	734	23/07/2002	19500		3	3	SALES	BIRMINGHAM
936	CASSY	ADMIN	734	23/07/2002	19500		3	4	OPERATIONS	LEEDS
912	HAYES	ADMIN	824	04/06/2001	21000		2	1	ACCOUNTIN	LONDON
912	HAYES	ADMIN	824	04/06/2001	21000		2	2	RESEARCH	YORK
912	HAYES	ADMIN	824	04/06/2001	21000		2	3	SALES	BIRMINGHAM
912	HAYES	ADMIN	824	04/06/2001	21000		2	4	OPERATIONS	LEEDS
557	BELL	SALES	734	26/03/2000	22500	500	3	1	ACCOUNTIN	LONDON
557	BELL	SALES	734	26/03/2000	22500	500	3	2	RESEARCH	YORK

With many more records not shown.

Activity: Try this query out and verify that it performs as suggested

In fact, the Cartesian Product merges every row from every table together – the EMP table contains 14 records, the DEPT table contains 4 records, hence the final query results in 14*4 = 56 records. The database cannot assume (or deduce) how the table should be connected. To do this an extra term must be added to the WHERE clause, specifying which two (or more) columns should contain values that are to be compared in some way (typically using equality '=').

With this example, it is clear that there are two columns that should be matched to produce the correct results – the EMP table contains a DEPTNO column, the DEPT table contains a DEPTNO. Only those rows which contain the same value should be retained.

A correct version of the SELECT clause for this example would look like this:

```
select *
from dept, emp
where emp.deptno=dept.deptno;
```

Notice how we have to refer to the different DEPTNO attributes using the **tablename.columnname** syntax. This is required as the two tables share a same named column heading DEPTNO.

EMPNO	ENAME	JOB	MGR	HIREDATE	SAL	COMM	emp.DEPTNO	dept.DEPTNO	DNAME	LOC
405	MARCH	ADMIN	938	13/06/1997	18000		2	2	RESEARCH	YORK
936	CASSY	ADMIN	734	23/07/2002	19500		3	3	SALES	BIRMINGHAM
912	HAYES	ADMIN	824	04/06/2001	21000		2	2	RESEARCH	YORK
557	BELL	SALES	734	26/03/2000	22500	500	3	3	SALES	BIRMINGHAM
690	AHMAD	SALES	734	05/12/1997	22500	1400	3	3	SALES	BIRMINGHAM
970	BLACK	ADMIN	818	21/11/1997	23000		1	1	ACCOUNTIN	LONDON
880	TURNER	SALES	734	04/06/2001	25000	0	3	3	SALES	BIRMINGHAM
535	BYRNE	SALES	734	15/08/1997	26000	300	3	3	SALES	BIRMINGHAM
818	POLLARD	MANAG	875	14/05/2000	34500		1	1	ACCOUNTIN	LONDON
734	COX	MANAG	875	11/06/2002	38500		3	3	SALES	BIRMINGHAM
602	BIRD	MANAG	875	31/10/1997	39750		2	2	RESEARCH	YORK
824	REES	ANALY	602	05/03/2000	40000		2	2	RESEARCH	YORK
938	GIBSON	ANALY	602	05/12/1997	40000		2	2	RESEARCH	YORK
875	PARKER	PRESID		09/07/2002	60000		1	1	ACCOUNTIN	LONDON

Here it is clear from the two DEPTNO columns that the records have been matched in the correct sequence.

In Relational Algebra this would be written as a combination of Selection and Cartesian Product:

$$\sigma_{emp.deptno=dept.deptno} (EMP \times DEPT)$$

As this operation is performed so frequently, it has its own name - a Cartesian product with an appropriate Selection Operation is called an **Inner Join**.

Activity: Try out the refined query and verify that it produces this result.

To join *three* tables it is normally necessary to specify *two* join conditions, *four* tables usually require *three* join conditions etc.

Temporary labels may be specified in the from clause to save repeating the full table names repeatedly in the query:

```
SELECT *
from emp e, dept d
where e.deptno=d.deptno;
```

Other Boolean operators to specify a further subset of the selection can be appended as normal:

```
SELECT *
from emp e, dept d
where e.deptno=d.deptno
and d.dname="Accounting";
```

Inner Join and Cartesian Product examples

Activity: Type these example queries in and verify that they produce similar results

Examples

Display Employee Name, Department No and Location where Employees work

```
SELECT ename, emp.deptno, loc
from emp, dept
where emp.deptno=dept.deptno;
```

ename	deptno	loc
MARCH	2	YORK
CASSY	3	BIRMINGHAM
HAYES	2	YORK
BELL	3	BIRMINGHAM
AHMAD	3	BIRMINGHAM
BLACK	1	LONDON
TURNER	3	BIRMINGHAM
BYRNE	3	BIRMINGHAM
POLLARD	1	LONDON
COX	3	BIRMINGHAM
BIRD	2	YORK
REES	2	YORK
GIBSON	2	YORK
PARKER	1	LONDON

Note that the department number must be prefixed with the tablename **emp** – this is to clarify which department number is included in the output.

Find out where the President is based

```
SELECT ename, emp.deptno, loc
from emp, dept
where emp.deptno=dept.deptno
and job = "President";
```

ename	deptno	loc
PARKER	1	LONDON

Find all the employees in the sales department

```
SELECT ename, emp.deptno, loc
from emp, dept
where emp.deptno=dept.deptno
and dname="Sales";
```

ename	deptno	loc
CASSY	3	BIRMINGHAM
BELL	3	BIRMINGHAM
AHMAD	3	BIRMINGHAM
TURNER	3	BIRMINGHAM
BYRNE	3	BIRMINGHAM
COX	3	BIRMINGHAM

Exercises – Inner Join, Selection and Projection

In the following exercises, the query must be specified to produce the suggested result. There are spaces for you to write the SQL query and Relational Algebra (where appropriate). Use the AS command to get correct column headings in SQL.

1. Display the employee name and location of employment

SQL:

Ename	loc
MARCH	YORK
CASSY	BIRMINGHAM
HAYES	YORK
BELL	BIRMINGHAM
AHMAD	BIRMINGHAM
BLACK	LONDON
TURNER	BIRMINGHAM
BYRNE	BIRMINGHAM
POLLARD	LONDON
COX	BIRMINGHAM
BIRD	YORK
REES	YORK
GIBSON	YORK
PARKER	LONDON

In Relational Algebra:

2. Display the Employee name and salary for employees working in York

SQL:

Ename	sal
MARCH	18000
HAYES	21000
BIRD	39750
REES	40000
GIBSON	40000

In Relational Algebra:

3. Display the Employee name and job for everyone working in research

SQL:

ename	job
MARCH	ADMIN
HAYES	ADMIN
BIRD	MANAGER
REES	ANALYST
GIBSON	ANALYST

In Relational Algebra:

4. Display all the employees who either work in York or Leeds

SQL:

Ename
MARCH
BIRD
REES
HAYES
GIBSON

In Relational Algebra:

Hint: In the same way that $4+5*2$ is 14 (rather than 18), precedence rules apply in logic, so that AND operations are performed before OR operations. To get the correct output, you may need to add brackets around certain parts of the SQL expression

5. (HARD) Display every employee along with their manager

SQL:

employee	manager
MARCH	GIBSON
CASSY	COX
HAYES	REES
BELL	COX
AHMAD	COX
BLACK	POLLARD
TURNER	COX
BYRNE	COX
POLLARD	PARKER
COX	PARKER
BIRD	PARKER
REES	BIRD
GIBSON	BIRD

In Relational Algebra:

Hint: you can use the AS reserved word to create a temporary name for a table, i.e.

...from emp as employee ...